


AVAILABLE OPTIONS:

GS120GM

Guard for (standard) type MP and optional suffix TW/KR/MO 40mm mushroom operator, lockable

(RED METAL GUARD)



GS120 with PILLHCOV1

One Clear Hinged Cover fits all one device/push button model series and one-two device/Power Control series, provision for padlock/seal




GS120MO

Momentary 40mm mushroom model



GS120KR


Key Release 40mm mushroom model with two keys, key required to reset.



GS120GM(y)

Guard for (standard) type MP and optional suffix TW/KR/MO 40mm mushroom operator, lockable

(YELLOW NONMETALLIC GUARD)




GS120TW

Maintained "TURN TO RESET" 40mm mushroom model



GS120MDYCLM-30


Switch 12 A @ 120V AC
10 V @ 24v DC
(pilot duty-inductive loads).
Start/Stop Motors:
1.5 PH @ 120V AC
3PH @ 240V AC
10A FLA/60A LRA @ 24V DC.
Available in N.O. or N.C. configuration.
Terminals accept up to 10 AWG wires.



UL LISTED 9F36 (CANADA)

GS120XD

Extra depth option: Capacity 6 single pole contact block.
Extra depth version type MP(standard), also available for all optional suffix TW/KR/MO.



PILNCCB		PILNOCB	
----------------	---	----------------	--

RATED OPERATIONAL CHARACTERISTICS CONFORMING TO EC/EN 60947-5-1	AC SUPPLY: UTILIZATION CATEGORY AC-15	STANDARD BLOCKS (SINGLE OR DOUBLE) WITH SCREW CLAMP TERMINALS: A600: Ue=600Vac AND Ie=1.2 A OR Ue=240 Vac AND Ie= 3 A OR Ue = 120 Vac AND Ie = 6 A CONTINUOUS THERMAL CURRENT 10 A
	DC SUPPLY: UTILIZATION CATEGORY DC-13	STANDARD SINGLE OR DOUBLE BLOCKS WITH SCREW CLAMP TERMINALS: Q600: Ue= 600VdC AND Ie = 0.1 A 24 Vdc