










# AVAILABLE OPTIONS:

<p><b>FS120MPGM</b></p> <p><b>FS120GM</b></p> <p>Guard for (standard) type MP and optional suffix TW/KR/MO 40mm mushroom operator, lockable</p> <p><b>(RED METAL GUARD)</b></p>		<p><b>FS120 with PILCHCOV1</b></p> <p>One Clear Hinged Cover fits all one device/push button model series and one-two device/Power Control series, provision for padlock/seal</p>	
<p><b>FS120MO</b></p> <p>Momentary 40mm mushroom model</p>		<p><b>FS120KR</b></p> <p>Key Release 40mm mushroom model with two keys, key required to reset.</p>	
<p><b>FS120MPGM(y)</b></p> <p>Guard for (standard) type MP and optional suffix TW/KR/MO 40mm mushroom operator, lockable</p> <p><b>(YELLOW NONMETALLIC GUARD)</b></p>		<p><b>FS120TW</b></p> <p>Maintained "TURN TO RESET" 40mm mushroom model</p>	
<p><b>FS120MDYCLM-30</b></p> <p>Switch 12 A @ 120V AC 10 V @ 24v DC (pilot duty-inductive loads). Start/Stop Motors: 1.5 PH @ 120V AC 3PH @ 240V AC 10A FLA/60A LRA @ 24V DC. Available in N.O. or N.C. configuration. Terminals accept up to 10 AWG wires.</p> <p></p>		<p><b>FS120XD</b></p> <p>Extra depth option: Capacity 6 single pole contact block. Extra depth version type MP(standard),also available for all optional suffix TW/KR/MO.</p>	

<p><b>PILNCCB</b></p> 		<p><b>PILNOCB</b></p>
---	--	-----------------------

<p><b>FS120MPGM(y)</b> RATED OPERATIONAL CHARACTERISTICS CONFORMING TO EC/EN 60947-5-1</p>	<p><b>AC SUPPLY:</b> UTILIZATION CATEGORY AC-15</p>	<p><b>STANDARD BLOCKS (SINGLE OR DOUBLE) WITH SCREW CLAMP TERMINALS:</b> A600: Ue=600Vac AND Ie=1.2 A OR Ue=240 Vac AND Ie= 3 A OR Ue = 120 Vac AND Ie = 6 A CONTINUOUS THERMAL CURRENT 10 A</p>	
	<p><b>DC SUPPLY:</b> UTILIZATION CATEGORY DC-13</p>	<p><b>STANDARD SINGLE OR DOUBLE BLOCKS WITH SCREW CLAMP TERMINALS:</b> Q600: Ue= 600VdC AND Ie = 0.1 A</p>	<p>24 Vdc</p> <p>0.5 A</p>