

# AVAILABLE OPTIONS:

**HVAC120GM**

Guard for (standard) type MP and optional suffix TW/KR/MO 40mm mushroom operator, lockable

(RED METAL GUARD)



**HVAC120 with PILCLHCOV1**

One Clear Hinged Cover fits all one device/push button model series and one-two device/Power Control series, provision for padlock/seal



**HVAC 120MO**

Momentary 40mm mushroom model



**HVAC120KR**

Key Release 40mm mushroom model with two keys, key required to reset.



**HVAC120GM(y)**

Guard for (standard) type MP and optional suffix TW/KR/MO 40mm mushroom operator, lockable

(YELLOW NONMETALLIC GUARD)



**HVAC120TW**

Maintained "TURN TO RESET" 40mm mushroom model



**HVAC120MDYCLM-30**

Switch 12 A @ 120V AC  
10 V @ 24v DC  
(pilot duty-inductive loads).  
Start/Stop Motors:  
1.5 PH @ 120V AC  
3PH @ 240V AC  
10A FLA/60A LRA @ 24V DC.  
Available in N.O. or N.C. configuration.  
Terminals accept up to 10 AWG wires.



UL LISTED 9F36 (CANADA)

**HVAC120XD**

Extra depth option: Capacity 6 single pole contact block.  
Extra depth version type MP(standard), also available for all optional suffix TW/KR/MO.



<b>PILNCCB</b>		<b>PILNOCB</b>	
----------------	---	----------------	--

<b>RATED OPERATIONAL CHARACTERISTICS CONFORMING TO EC/EN 60947-5-1</b>	<b>AC SUPPLY:</b> UTILIZATION CATEGORY AC-15	<b>STANDARD BLOCKS (SINGLE OR DOUBLE) WITH SCREW CLAMP TERMINALS:</b> A600: Ue=600Vac AND Ie=1.2 A OR Ue=240 Vac AND Ie= 3 A OR Ue = 120 Vac AND Ie = 6 A CONTINUOUS THERMAL CURRENT 10 A
	<b>DC SUPPLY:</b> UTILIZATION CATEGORY DC-13	<b>STANDARD SINGLE OR DOUBLE BLOCKS WITH SCREW CLAMP TERMINALS:</b> Q600: Ue= 600VdC AND Ie = 0.1 A 24 Vdc