



Datasheet

Standalone Heatpump Controller (PL-C1050-HPS)

Description

The C1050 HPS heat pump controller is designed to control a variety of heatpump units and systems. The on-board microcontroller offers precise digital control to maximize performance. The available control sequences are fully configurable, either locally or remotely, using free software. The C1050 HPS uses PI (Proportional-Integral) control loops to optimize heatpump management and offers a variety of functions such as economizer, preheating, emergency auxiliary heating and more.

Features

- Designed for unitary systems using a single space temperature sensor
- Works in Air-To-Air mode or Water-To-Air mode (configurable)
- Remote monitoring and configuration with FREE Prolon Focus software
- Stand-alone or networked (up to 127 nodes)
- Proportional-Integral (PI) control loops maximize performance
- 4 digital outputs and 1 analog output equipped with resettable fuses
- Built-in protection sequences with configurable temperature limits and minimum delays
- Control up to 2 compressor stages or 2 stage auxiliary heating stages
- Configurable unoccupied mode sequences

Technical Specifications

- **Supply:** 24 VAC \pm 10%, 50/60 Hz, Class 2
- **Power:** 2 VA (consumption), 32 VA (input)
- **Inputs:** 4 configurable inputs with selectable functions (outside temp / return temp / supply temp / water intake temp / night setback / proof of fan / alarm)
- **Digital Outputs:** 4 triac outputs, 10-30 VAC source, 300 mA max (resettable fuse)
- **Analog Output:** 1 output 0-10 VDC / 2-10 VDC / 0-5 VDC, 40 mA max (resettable fuse)
- **Indication lights (LED):** State of each output / Communication / Power / State of microprocessor
- **Microprocessor:** PIC18F6722, 8 bits, 40 MHz, 128KB FLASH memory
- **Casing:** Molded ABS, UL94-HB
- **Communication:** Modbus RTU (RS485) up to 127 nodes
- **Baud Rates:** 9600, 19200, 38400, 57600, 76800, 115200
- **Connection:** Removable screw-type terminal blocks (16 AWG max)
- **Dimensions:** 6.2" x 5.2" x 2.5" (157mm x 132mm x 64mm)
- **Weight:** 0.85 lbs (0.39 kg)
- **Environment:** -4 to 122 °F (-20 to 50 °C) Non-Condensing
- **Certification:** UL916 Energy Management Equipment, CAN/CSA-C22.2, RoHS, FCC part 15: 2012 class B