

PROLON



---

# QUICK START **GUIDE**

C1050 SERIES

---

[www.proloncontrols.com](http://www.proloncontrols.com) | [info@proloncontrols.com](mailto:info@proloncontrols.com)

17 510 rue Charles, Suite 100, Mirabel, QC, J7J 1X9

REV. 2.0  
PL-QCK-C1050-EN


## Table of Contents

Staged Boiler Controller (PL-C1050-BLR) .....	4
Modulating Boiler Controller (PL-C1050-BLR) .....	6
Chiller Controller (PL-C1050-CHL) .....	8
Fan Coil Unit Controller - Two-Pipe System (PL-C1050-FCU) .....	10
Fan Coil Unit Controller - Four Pipe System (PL-C1050-FCU) .....	12
FlexIO Controller (PL-C1050-FLX) .....	14
Heatpump Controller (PL-C1050-HP & PL-C1050-HPS) .....	16
Humidity Controller (PL-C1050-HU) .....	18
Rooftop Controller (PL-C1050-RTU & PL-C1050-RTUS) .....	20
Water Loop Controller (PL-C1050-WLC) .....	22
Compliance .....	24
Technical Specifications .....	24

© Copyright 2021 Proton. All rights reserved.

No part of this document may be photocopied or reproduced by any means, or translated to another language without prior written consent of Proton. All specifications are nominal and may change as design improvements are introduced. Proton shall not be liable for damages resulting from misapplication or misuse of its products. All trademarks are the property of their respective owners.

# Staged Boiler Controller (PL-C1050-BLR)




-4 to 122 °F (-20 to 50 °C) Non-condensing

cULus Listed; UL 916 Energy Management Equipment, File E364757, Vol.1



# Modulating Boiler Controller (PL-C1050-BLR)




-4 to 122 °F (-20 to 50 °C) Non-condensing

cULus Listed; UL 916 Energy Management Equipment, File E364757, Vol.1




# Chiller Controller (PL-C1050-CHL)




-4 to 122 °F (-20 to 50 °C) Non-condensing


cULus Listed; UL 916 Energy Management Equipment, File E364757, Vol.1







# FlexIO Controller (PL-C1050-FLX)




-4 to 122 °F (-20 to 50 °C) Non-condensing

cULus Listed; UL 916 Energy Management Equipment, File E364757, Vol.1





# Heatpump Controller (PL-C1050-HP & PL-C1050-HPS)




-4 to 122 °F (-20 to 50 °C) Non-condensing

cULus Listed; UL 916 Energy Management Equipment, File E364757, Vol.1



# Humidity Controller (PL-C1050-HU)




-4 to 122 °F (-20 to 50 °C) Non-condensing

cULus Listed; UL 916 Energy Management Equipment, File E364757, Vol.1



# Rooftop Controller (PL-C1050-RTU & PL-C1050-RTUS)




-4 to 122 °F (-20 to 50 °C) Non-condensing

cULus Listed; UL 916 Energy Management Equipment, File E364757, Vol.1



# Water Loop Controller (PL-C1050-WLC)



-4 to 122 °F (-20 to 50 °C) Non-condensing

cULus Listed; UL 916 Energy Management Equipment, File E364757, Vol.1



## Compliance

- cULus Listed; UL 916 Energy Management Equipment, File E364757, Vol.1
- FCC Compliant to CFR47, Part 15, Subpart B, Class B
- Industry Canada (IC) Compliant to ICES-003, Issue 5: CAN ICES-3 (B) / NMB-3(B)
- RoHS Directive (2002/95/EC)

### FCC User Information

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

### Industry Canada

This Class (B) digital apparatus meets all the requirements of the Canadian Interference-Causing Equipment regulations.

Cet appareil numérique de la Classe (B) respecte toutes les exigences du Règlement sur le matériel brouilleur du Canada.

## Technical Specifications

**Supply:** 24 VAC  $\pm$ 10%, 50/60 Hz, Class 2

**Power:** 2 VA (consumption), 32 VA (Input)