



# Low-Voltage Fan Coil Room Controller: Stand Alone, RH sensor & control, Floating or on-off, Commercial/Override

SE7350C5045

•			•	
N	И	а	ı	n

Product name	SE7000 Series
Device short name	SE7300
Product or component type	Room controller
Device application	Low voltage fan coil
Net weight	0.34 kg
AWG gauge	AWG 22AWG 18
Height	124.97 mm
Width	86.87 mm
Directives	89/336/EEC - electromagnetic compatibility
Depth	29.97 mm
Ambient air temperature for operation	-050 °C
Market segment	Small commercial
Ambient air temperature for storage	-3050 °C
Measurement accuracy	Humidity: +/- 5 %, 2080 % RH (non-condensing) Temperature: +/- 0.9 °F, (at 70 °F typically calibrated)
Product certifications	CE C-Tick conforming to AS/NZS CISPR 22 FCC conforming to CFR 47 part 15 class A UL listed file E27734 CCN XPAX UL listed file E27734 CCN XPAX7
Information displayed	Temperature: - 40122 °F
Network frequency	50 Hz 60 Hz
Communication port protocol	Standalone (network ready)
Temperature setting range	432 °C heating -17 °C per step 1238 °C cooling
Humidity setting range	Humidification: 1090 % Dehumidification: 1595 %
Calibration certificate	1 pt
Output type	2 xuniversal 1 xdigital

Input type	1.0 x dry contact
Output current	1 A relay output
	3 A relay output (inrush)
Standards	CSA C22.2 No 24
	FCC part 15 Subpart B
	UL 873
	ICES-003
Relative humidity	095 % RH, non-condensing
[Us] rated supply voltage	1030 V AC 50/60 Hz
Sensor type	Single point calibrated bulk polymer RH sensor humidity
••	10 kOhm T2 NTC thermistor temperature
Range	EcoStruxure Building Expert
Economizer	No
Humidity control	Yes
PIR cover	No
Scheduling	No
Complementary	
Device presentation	Without cover

Device presentation	Without cover
Rated operational power in VA	2 VA
Connections - terminals	Screw terminal
Range compatibility	EcoStruxure Building Expert communication card EcoStruxure Building Expert sensor EcoStruxure Building Expert temperature sensor EcoStruxure Building Expert relay EcoStruxure Building Expert sensor coverplate

#### **Environment**

Electrical insulation class Class II

### **Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10.0 cm
Package 1 Width	15.0 cm
Package 1 Length	5.0 cm
Package 1 Weight	200.0 g

## Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

#### Recommended replacement(s)