

# Product data sheet

Specifications



## Line-Voltage Fan Coil Room Controller: BACnet MS/TP, ZigBee Embedded, RH sensor & control, IP ready, PIR motion sensor, White Case/Fascia

SER8350A5B11P

### Main

Product name	SE8000 Series
Device short name	SER8300
Product or component type	Room controller
Device application	Line voltage fan coil
Net weight	340 g
AWG gauge	AWG 24...AWG 18
Height	120 mm
Width	86 mm
Directives	2014/30/EU - electromagnetic compatibility 2014/35/EU - low voltage directive 2014/53/EU - radio equipment directive
[In] rated current	4 A
Depth	25 mm
Ambient air temperature for operation	0...50 °C
Market segment	Lodging Small commercial Hotel Buildings Healthcare Non-critical buildings Office Residential School
Housing colour	White
Ambient air temperature for storage	-30...50 °C
Measurement accuracy	Temperature: +/- 0.5 °C, Humidity: +/- 5 %, 20...80 % RH (non-condensing) Humidity: +/- 10 %, 10...20 % (non-condensing) Humidity: +/- 10 %, 80...90 % (non-condensing)
Information displayed	Temperature: - 40...122 °F
Network frequency	50 Hz 60 Hz
Communication port protocol	BACnet MS/TP Modbus RTU Zigbee Pro
Temperature setting range	12...37.5 °C cooling

4.5...32 °C heating

<b>Input voltage</b>	0...10 V DC
<b>Output voltage</b>	24 V AC for relay output 0...10 V DC for analog output
<b>Relative humidity</b>	0...95 %
<b>Output current</b>	1 A relay output 3 A relay output (inrush)
<b>Input type</b>	2 x dry contact 5 x analog
<b>Sensor type</b>	10 kOhm T2 NTC thermistor temperature Space RH sensor humidity
<b>Output type</b>	5 x relay output 4 x universal
<b>[Us] rated supply voltage</b>	7 V DC 50/60 Hz +/- 10 %
<b>Standards</b>	EN/IEC 60730-1 EN/IEC 60730-2-9 EN/IEC 60730-2-13 CSA E60730-2-9 UL 60730-2-9 UL 60730-2-13 ICES-003 FCC part 15 Subpart B ETSI EN 300 328:v2.1.1 ETSI EN 301 489-1:v1.9.2 FCC part 15 Subpart C ETSI EN 301 489-17:v2.2.1, 2012 RSS 247
<b>Humidity setting range</b>	30...95 %
<b>Range</b>	EcoStruxure Building Expert
<b>Economizer</b>	No
<b>Humidity control</b>	Yes
<b>PIR cover</b>	Yes
<b>Scheduling</b>	Yes

## Complementary

<b>Surface finish</b>	Matt
<b>Surface treatment</b>	Untreated
<b>Function available</b>	Fan control HVAC control Available with CO2/RH/T Brightness sensor Changes can be made directly over display Code lock function Easily configurable Firmware update by USB

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	8.6 cm
<b>Package 1 Width</b>	12.0 cm
<b>Package 1 Length</b>	2.5 cm
<b>Package 1 Weight</b>	245.0 g

## Offer Sustainability

<b>REACH Regulation</b>	<a href="#">REACH Declaration</a>
<b>EU RoHS Directive</b>	Compliant <a href="#">EU RoHS Declaration</a>

---

<b>Mercury free</b>	Yes
<b>China RoHS Regulation</b>	<a href="#">China RoHS declaration</a>
<b>RoHS exemption information</b>	Yes
<b>California proposition 65</b>	WARNING: This product can expose you to chemicals including: LEAD, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

---

**Recommended replacement(s)**