

PG Series

Gauge Pressure Transducer

Stainless Steel Wet Media 1/4" MNPT 0-5VDC or 4-20mA outputs



DESCRIPTION

This PG Series is a rugged and accurate gauge pressure sensor. It is compatible with a wide variety of liquids and gases. Whether measuring hydraulic pressure in a manifold or corrosive liquids and gases such as sea water or hydrogen, the PG series industrial pressure sensor provides a thick diaphragm to maintain long-term stability.

APPLICATIONS

- Refrigeration Pump Controls
- Chillers
- Freon and Ammonia Cooling Systems
- CO2 Systems
- Building Controls
- Water Pressure Systems
- Boiler Controls
- Environmental Test Chambers

FEATURES

Versatile

- Compact, robust package
- 1/4" MNPT
- Chemical Compatibilities: Any gas or liquid compatible with 316L stainless steel.
- IP65


High Reliability...fewer call backs

- Burst pressure 5X full scale
- Reverse voltage protected
- Rugged stainless steel construction

Superb Accuracy

< ±0.25% BFSL @ room temperature (Accuracy includes non-linearity, hysteresis & non-repeatability)





ELECTRICAL DATA		
Output	4-20mA	0-5VDC
Power Supply	12-28VDC	12-28VDC
Output Load	250-500 Ohms	5K Ohms min.
Current Consumption	20mA, typical	<20mA

ENVIRONMENTAL DATA	
Temperature	
Operating	-20 to 85°C (-4 to 185°F)
Storage	-40 to 125°C (-40 to 257°F)
Thermal Limits	
Compensated Range	0 to 60°C (32 to 140°F)
TC Zero	<±1% of FS
TC Span	<±1% of FS
Other	
Rating	IP-65 (housing only)

PERFORMANCE @ 25°C (77°F)		
Accuracy (1)	<±0.25% BFSL	
Stability (1 year)	±0.25% FS, typical	
Over Range Protection	2X Rated Pressure	
Burst Pressure	5X	
Pressure Cycles	> 100 Million	
(1) Accuracy includes non-linearity bysteresis & non-repeatability		

(1) Accuracy includes non-linearity, hysteresis & non-repeatability

WIRING CONNECTIONS	
0-5 VDC Models	3-wire voltage
4-20mA Models	2-wire loop powered



Warning: Refer to installation instructions that accompany product and heed all safety instructions.